



KL FRESNEL 6 CW PO™

KL FRESNEL 6 CW PO™ is a 150W 5,600K Cool White LED fresnel on par with compatible tungsten halogen models. Features include manual and DMX control, 15° to 38° wide manual zoom, manual and DMX controlled dimmer and shutter, dimmer and zoom rotary dials, smooth 16-bit selectable dimming modes and curves, LED refresh rate frequency adjustment for flicker free operation for TV and FILM, removable barn doors (included), RDM (remote device management) protocol support, 3/5pin DMX and powerCON TRUE1 in/out connections, 4 button control panel, LCD menu display, multiple unit power linking, a universal auto switching power supply (100-240v), gel frame and rotating bar doors (included), and can be pole operated. (pole not included)

FEATURES

- 150W 5,600K Cool White LED Engine**
- Output On Par with Tungsten Halogen Models**
- 15° to 38° Wide Manual Zoom**
- Manual and DMX Controlled Dimmer and Shutter**
- Dimmer and Zoom Rotary Dials**
- Smooth 16-bit Selectable Dimming Modes and Curves**
- LED Refresh Rate Adjustment**
- Flicker Free Operation for TV and FILM**
- RDM (Remote Device Management)**
- Gel Frame and Rotating Barn Doors (included)**
- Pole Operated (pole not included)**

Specifications subject to change without notice ©Elation Professional 03/17/19

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu

SPECIFICATIONS

SOURCE

150W 5,600K Cool White LED
 50,000 Hour Average LED Life*

*May vary depending on several factors including but not limited to:
 Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

PHOTOMETRIC DATA

(pending)

EFFECTS

15° - 38° Wide Manual Zoom
 Electronic Dimmer and Strobe
 Variable 16-bit Dimming Modes and Curves

COLOR

Cool White 5,600K

CONTROL / CONNECTIONS

Manual and DMX Controlled Dimmer and Shutter
 Dimmer and Zoom Rotary Dials
 Pole Operated (pole not included)
 (5) DMX Channel Modes (1 / 2 / 3 / 4 / 5)
 4 Button Control Panel LCD Menu Display
 RDM (Remote Device Management)
 Adjustable LED Refresh Rate
 3/5pin DMX and powerCON TRUE1 In/Out

SIZE / WEIGHT

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz
 180W Max Power Consumption
 Multiple Unit Power Linking
 5°F to 113°F (-15°C to 45°C)

INCLUDED ITEMS

Gel Frame and Rotating Barn Doors
 powerCON TRUE1 Power Cable
 Barn Doors and Fixture Safety Cables

APPROVALS / RATINGS



PHOTOMETRIC DATA (pending)

DIMENSIONAL DIAGRAMS

ORDERING INFORMATION

1236100177	KL FRESNEL 6 CW PO
1621000071	PC 1m Powercon True1 Link Cable (Additional cable lengths available)



Specifications subject to change without notice ©Elation Professional 03/02/19

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
 323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
 +31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu