



Visit product page



FOS SPARK JET PRO V2

L005544

The best sparkle machine with RDM function and height adjustment channel! Adjustable Height 1.5-5M, Maximum Single Continuous Duration 30s, Heat Up Time 5 Minutes, seetronic connectors, consumption 20-25g/Minute.

TECHNICAL DETAILS

Technical Specifications

Power supply: 200/240V, 50/60 Hz.

Nominal power consumption: 600 W.

Heat up time: 5 minutes.

Powder tank capacity: 150g.

Adjustable height from 1,5 to 5 meters.

Powder consumption: 20/25g per minute (maximum).

Maximum single continuous duration: 30s.

Controlled via DMX512.

Remote Control included

RDM support.

1,6 meter power cord (Seetronic).

Net weight: 8Kg.

Gross weight: 10Kg.

Dimensions: 215 x 213 x 262 mm.

Package dimensions: 270 x 250 x 330 mm.

Granule: Spark Fabrika Granule

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FC-TP-PDC-5

Professional TruePowercon/ DMX cable 5 meter.



FC-TP-PDC-3

Professional TruePowercon/ DMX cable 3 meter.



FC-TP-PDC-1.5

Professional TruePowercon/ DMX cable 1.5 meter.



FOS Case Spark Jet PRO

Flight case with wheels for 4 pcs Spark Jet PRO wi



FOS Spark Powder Normal

Titanium Powder 150 gr and RFID card for Spark Jet



