



Visit product page



FOS WASH Q7

L005299

Wash / Beam moving head , Zoom 6-60° , .7x15w 4-IN-1 RGBW leds ,Pixel Control , CTO,CTB, linear colour temperature 2,700-8,000K preset , 14/20/44/50 DMX channels USITT DMX-512.

TECHNICAL DETAILS

Light source / Optics

Light source: 7x 15 Watt 4 in 1 RGBW LEDs

Life span: 50,000 hours approx.

Beam angle: 6°-60° with motorized zoom.

Flat, uniform lighting field.

Effects

High quality RGBW color mixing system.

Independent pixel control and pixel / chase effects with adjustable speed.

Linear color temperature change 2700 - 8000 K.

Tungsten simulation from 2800 - 3200 K.

14 pre-programmed colors.

32 pre-programmed dynamic patterns.

32 pre-programmed static patterns.

7 built in auto programs accessible via DMX.

Control

DMX512 control with 14, 20, 44 & 50 channels.

Auto, Master/Slave & Sound modes.

Installation / Dimension details.

630° /540° /360° PAN and 270°/180° /90° TILT movement options.

16bit movement resolution with feedback.

20°C / 45°C min & max ambient operating temperature.

Temperature sensors and fan control.

IP20: for indoor use only.

Maximum noise level at 1m: 46 dB.

Dimensions: 280 x 170 x 335 mm.

Packing dimensions: 420 x 380 x 290 mm.

Net weight: 6,6 Kg.

Gross weight: 8,34 Kg.

Photometric Data

Measured Distance: 5 meters.

Full on (RGBW) Minimum Zoom 6°

Illuminance (lx): 2165

CRI (Ra): 74

TLCI (Qa): 53.0

Flicker Frequency (Hz): 139

Flicker(%): 0

Full On (RGBW) Maximum Zoom 60°

Illuminance (lx): 166

CRI (Ra): 79

TLCI (Qa): 54.8

Flicker Frequency (Hz): 109

Flicker(%): 2

See photometrics for each color and beam angles in the Documents tab.

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FC-PDC-3

Professional PowerCon /
DMX cable 3 meter,



FOS SUPER CLAMP 200

Professional clamp for
fixtures lifting weight 200



FOS SUPER CLAMP 200
BLACK

Professional clamp for
fixtures lifting weight 200



Fos Case Wash Q7

Flight case with wheels for
4 pcs Wash Q7

